# Buy it for looks. Buy it for life.®

# Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Designed to be installed through 2, 1-1/4" and 1, 1" min. dia. holes 8" on center
- 1/2" copper connections
- Adaptable for non-8" centers

#### OPERATION

- Maximum handle rotation angle is 90° to full on for either handle
- Rotate hot side counterclockwise to open and clockwise to close
- Rotate cold side clockwise to open and counterclockwise to close

#### Flow

• Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi


#### CARTRIDGE

1224 cartridge design nonmetallic/nonferrous and stainless steel material
 STANDARDS

- Third party certified to WaterSense® CSA B-125.1, ASME A112.18.1 and
- all applicable requirements referenced therein including NSF 61/9
  Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations




## WEYMOUTH<sup>™</sup> Two-Handle Wall Mount Faucet

Model: TS42106 series (Lever Handle) TS42112 series (Cross Handle)

### Valve: 9400





# **CRITICAL DIMENSIONS**

(DO NOT SCALE)